



Trade Mark Reg.No.181523  
Ind.Reg 106656

## **TECHNICAL DATA SHEET**

---

### **PRIMER P6608**

---

#### **DESCRIPTION**

It is highly recommended to be used for natural leather soles and leather shoe uppers, to achieve high performance adhesion and good resistance to water and high temperature for long life shoe duration.

#### **CHARACTERISTICS**

- |                                     |  |
|-------------------------------------|--|
| - Adhesive                          | monocomponent polyurethane                 |
| - Colour                            | semitransparent                            |
| - Viscosity at 20 deg Celsius       | 180 +/- 25cps                              |
| - Open time                         | fast                                       |
| - Specific weight at 20 deg Celsius | 0,79 +/- 0,005 Kg/dm <sup>3</sup>          |
| - Flammability                      | flammable                                  |
| - Chemical name                     | polyurethanes solution in organic solvents |

#### **APPLICATION**

Primer should be applied on the natural leather with a brush in order to enable the natural leather to absorb. Wait at least 30 minutes till primer crystallize. Then apply the adhesive

#### **STORAGE**

Shelf life: about 1 year if stored in well closed tins at 15 – 25 deg Celsius.

This information is to the best of our knowledge true and accurate. However, all recommendations or suggestions are made without guarantee, since the conditions of use are beyond our control.